



RED TRIGGER P/N 15.0003.11

FEATURES:

- * Body and sealing seat in polypropylene reinforced with fiberglass.
- * Pin in polypropylene reinforced with fiberglass.
- * Seal obtained by ball in tempered stainless steel AISI 420 and spring in stainless steel AISI 302
- * Seals in NBR
- * Rear fluid entry
- * Inlet / Outlet G 1/2 F
- * Max Pressure 25bar – 2.5Mpa (363psi)
- * Max Flow rate 70 l/min (18.5 USGp.m.)
- * Max temperature 50°C (120° F)
- * Weight 131 gr (4.62 oz.)

BLUE TRIGGER P/N 15.0003.12

FEATURES:

- * Body and sealing seat in polypropylene reinforced with fiberglass
- * Pin in stainless steel AISI 303
- * Seal obtained by ball in tempered stainless steel AISI 420 and spring in stainless steel AISI 302
- * Seals in VITON
- * Rear fluid entry
- * Inlet / Outlet G 1/2 F
- * Max Pressure 25bar – 2.5Mpa (363psi)
- * Max Flow rate 70 l/min (18.5 USGp.m.)
- * Max temperature 50°C (120° F)
- * Weight 131 gr (4.62 oz.)

GREY TRIGGER P/N 15.0013.12

FEATURES:

- * Body and sealing seat in polypropylene reinforced with fiberglass
- * Pin in stainless steel AISI 316
- * Seal obtained by ball in stainless steel AISI 316 and spring in stainless steel AISI 316
- * Seals in VITON
- * Rear fluid entry
- * Inlet / Outlet G 1/2 F
- * Max Pressure 25bar – 2.5Mpa (363psi)
- * Max Flow rate 70 l/min (18.5 USGp.m.)
- * Max temperature 50°C (120° F)
- * Weight 131 gr (4.62 oz.)

BROWN TRIGGER P/N 15.0015.12

FEATURES:

- * Body and sealing seat in polypropylene reinforced with stapled fiberglass
- * Pin in stainless steel AISI 316
- * Seal obtained by ball in stainless steel AISI 316 and spring in stainless steel AISI 316
- * Seals in VITON
- * Rear fluid entry
- * Inlet / Outlet G 1/2 F
- * Max Pressure 25bar – 2.5Mpa (363psi)
- * Max Flow rate 70 l/min (18.5 USGp.m.)
- * Max temperature 50°C (120° F)
- * Weight 131 gr (4.62 oz.)

**UNIVERSAL GUN FOR "ACID"
BLACK TRIGGER P/N 15.0003.41**

FEATURES:

- * Body and sealing seat in polypropylene reinforced with fiberglass.
- * Body and sealing seat in polypropylene reinforced with stapled fiberglass.
- * Pin in polypropylene reinforced with stapled fiberglass
- * Seal obtained by glass ball and spring stainless steel HASTELLOY.
- * Seals in EPDM
- * Rear fluid entry
- * Inlet / Outlet G 1/2 F
- * Max Pressure 25bar – 2.5Mpa (363psi)
- * Max Flow rate 70 l/min (18.5 USGp.m.)
- * Max temperature 50°C (120° F)
- * Weight 131 gr (4.62 oz.)

PURPLE TRIGGER P/N 15.0003.27

FEATURES:

- * Body and sealing seat in polypropylene
- * Pin in stainless steel AISI 303
- * Seal obtained by ball in tempered stainless steel AISI 420 and spring in stainless steel AISI 302
- * Seals in VITON
- * Rear fluid entry
- * Inlet / Outlet G 1/2 F
- * Max Pressure 15bar – 1.5Mpa (218psi)
- * Max Flow rate 70 l/min (18.5 USGp.m.)
- * Max temperature 40°C (104° F)
- * Weight 131 gr (4.62 oz.)

GREEN TRIGGER P/N 15.0014.12

FEATURES:

- * The gun always leaks a small quantity of fluid
Pressure loss: 2.8bar – 0.3Mpa (40psi) equal to 1–1.3 l/min 0.3 USGp.m.
- * Body and sealing seat in polypropylene reinforced with fiberglass
- * Pin in stainless steel AISI 316
- * Seal obtained by ball in stainless steel AISI 316 and spring in stainless steel AISI 316
- * Seals in VITON
- * Rear fluid entry
- * Inlet / Outlet G 1/2 F
- * Max Pressure 25bar – 2.5Mpa (363psi)
- * Max Flow rate 70 l/min (18.5 USGp.m.)
- * Max temperature 50°C (120° F)
- * Weight 131 gr (4.62 oz.)

YELLOW TRIGGER P/N 15.0003.10

FEATURES:

- * Body and sealing seat in polyamide reinforced with fiberglass
- * Pin in stainless steel AISI 303
- * Seal obtained by ball in tempered stainless steel AISI 420 and spring in stainless steel AISI 302
- * Seals in VITON
- * Rear fluid entry
- * Inlet / Outlet G 1/2 F
- * Max Pressure 60bar – 6Mpa (870psi)
- * Max Flow rate 70 l/min (18.5 USGp.m.)
- * Max temperature 60°C (140° F)
- * Weight 162 gr (5.7 oz.)